

Sub E1  
predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

outputting said rearranged data in time series.

2. **(Thrice Amended)** A de-interleaving method comprising the steps of:  
arranging received data having been interleaved in a matrix; and  
rearranging said data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

outputting said data in time series, thereby outputting said received data in the order before said received data was interleaved.

3. **(Thrice Amended)** An interleaving apparatus for interleaving data to be transmitted, comprising:

a storing unit for storing data to be transmitted; and

a control unit for controlling said storing unit so that said data to be transmitted is outputted from said storing unit with said data to be transmitted arranged in a matrix and said data to be transmitted rearranged by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data.

4. **(Thrice Amended)** The interleaving apparatus according to claim 3, wherein said control unit comprises a write control unit for generating a write address to be used to write said data to be transmitted in said storing unit with said data to be transmitted arranged in a matrix and rearranged by interchanging rows of the matrix according to a

Sub  
El  
predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and for writing said data to be transmitted in said storing unit, and said control unit reads said data to be transmitted stored in said storing unit in the order of addresses.

Sub  
El  
7. (Thrice Amended) The interleaving apparatus according to claim 3, wherein said control unit writes said data to be transmitted in said storing unit in the order of addresses, and said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data to read said data to be transmitted.

Sub  
El  
10. (Thrice Amended) A de-interleaving apparatus for de-interleaving received data, comprising:

a storing unit for storing said received data; and

a control unit for controlling said storing unit so that said received data is outputted from said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data.

11. (Thrice Amended) The de-interleaving apparatus according to claim 10, wherein said control unit comprises a write control unit for generating a write address to be used to write said received data in said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to write said received data, and said control unit reads said received data stored in said storing unit in the order of addresses.

14. (Thrice Amended) The de-interleaving apparatus according to claim 10, wherein said control unit writes said received data in said storing unit in the order of addresses, and said control unit has a read control unit for generating a read address to be used to read said received data in a state before said received data was interleaved from said storing unit by arranging said received data stored in said storing unit in a matrix and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and for reading said received data from said storing unit.

17. (Thrice Amended) An interleaving/de-interleaving system comprising an interleaving apparatus for interleaving data to be transmitted and a de-interleaving apparatus for receiving said transmitted data interleaved by said interleaving apparatus to de-interleave said transmitted data, wherein said interleaving apparatus outputs said data to be transmitted with said data to be transmitted arranged in a matrix and rearranged by interchanging rows of the matrix according to a predetermined order, each row

SW  
E1

representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and said de-interleaving apparatus outputs received data in a state before said transmitted data was interleaved by arranging said received data in a matrix and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data.

225

**18. (Thrice Amended)** An interleaving/de-interleaving apparatus for transmitting/receiving interleaved data to/from an opposite interleaving/de-interleaving apparatus, comprising:

an interleaving apparatus for outputting data to be transmitted to said opposite interleaving/de-interleaving apparatus with said data to be transmitted arranged in a matrix, and said data to be transmitted rearranged by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

a de-interleaving apparatus for outputting received data interleaved in said opposite interleaving/de-interleaving apparatus in a state before said received data was interleaved by arranging said received data in a matrix, and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data.

Sub  
E1

19. (Twice Amended) An interleaving apparatus for interleaving data to be transmitted, comprising:

a storing unit for storing data to be transmitted;

a control unit for controlling said storing unit so that said data to be transmitted is outputted from said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

wherein said control unit comprises a write control unit for generating a write address to be used to write said data to be transmitted in said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and for writing said data to be transmitted in said storing unit, and said control unit reads said data to be transmitted stored in said storing unit according to the order of addresses of said storing unit.

20. (Twice Amended) An interleaving apparatus for interleaving data to be transmitted, comprising:

a storing unit for storing data to be transmitted;

a control unit for controlling said storing unit so that said data to be transmitted is outputted from said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and

Sub E1  
interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

OS  
wherein said control unit comprises a write control unit for generating a write address to be used to write said data to be transmitted in said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and for writing said data to be transmitted in said storing unit so as to be read said data from said storing unit according to the order of addresses of said storing unit.

Sub E1  
23. (Twice Amended) An interleaving apparatus for interleaving data to be transmitted, comprising:

OK  
a storing unit for storing data to be transmitted;

a control unit for controlling said storing unit so that said data to be transmitted is outputted from said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

wherein said control unit writes said data to be transmitted in said storing unit according to the order of addresses of said storing unit, and said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of

said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to read said data to be transmitted.

**24. (Twice Amended)** An interleaving apparatus for interleaving data to be transmitted, comprising:

a storing unit for storing data to be transmitted;

206 a control unit for controlling said storing unit so that said data to be transmitted is outputted from said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

wherein said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted, written in the order of addresses of said storing unit, from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to read said data to be transmitted.

207 sub 21 **31. (Twice Amended)** A de-interleaving apparatus for de-interleaving received data, comprising:

a storing unit for storing said received data;

a control unit for controlling said storing unit so that said received data is outputted from said storing unit in a state before said received data was interleaved by

Sub  
EI

arranging said received data in a matrix and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

wherein said control unit comprises a write control unit for generating a write address to be used to write said received data in said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to write said received data, and said control unit reads said received data stored in said storing unit according to the order of addresses of said storing unit.

Q

**32. (Twice Amended)** A de-interleaving apparatus for de-interleaving received data, comprising:

a storing unit for storing said received data;

a control unit for controlling said storing unit so that said received data is outputted from said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and



Sub E1  
19  
wherein said control unit comprises a write control unit for generating a write address to be used to write said data to be transmitted in said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and for writing said data to be transmitted in said storing unit so as to be read said data from said storing unit according to the order of addresses of said storing unit.

Sub E1  
198  
**35. (Twice Amended)** A de-interleaving apparatus for de-interleaving received data, comprising:

a storing unit for storing said received data;

a control unit for controlling said storing unit so that said received data is outputted from said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

wherein said control unit writes said data to be transmitted in said storing unit according to the order of addresses of said storing unit, and said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by

Sub E1  
interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to read said data to be transmitted.

36. (Twice Amended) A de-interleaving apparatus for de-interleaving received data, comprising:

198  
a storing unit for storing said received data;

a control unit for controlling said storing unit so that said received data is outputted from said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data; and

wherein said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted, written in the order of addresses of said storing unit, from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and by interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to read said data to be transmitted.

29 Sub E1  
43. (Twice Amended) A transmitting apparatus with an interleaving function, comprising:

an error detection encoding unit for encoding an error detecting bit and for adding said error detecting bit to data to be transmitted;

an error correction encoding unit for adding an error correcting code, which is to be used for error correction, to said data to be transmitted, sent from said error detection encoding unit;

an interleaving unit which includes a storing unit for storing said data to be transmitted, from said error detection encoding unit, and a control unit for controlling said storing unit so that said data to be transmitted is outputted from said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data;

a signal assembling unit assembles interleaved data from said interleaving unit to form a signal format suited for transmission; and

a spreading unit for converting the signal sent from said signal assembling unit into a spread signal using a predetermined spreading code.

**44. (Twice Amended)** The transmitting apparatus with a interleaving function according to claim 43, wherein said control unit comprises a write control unit for generating a write address to be used to write said data to be transmitted in said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and for writing said data to be transmitted in said storing unit, and said control unit reads said data to be transmitted stored in said storing unit according to the order of addresses of said storing unit.

Sub  
E1

**45. (Twice Amended)** The transmitting apparatus with a interleaving function according to claim 43, wherein said control unit writes said data to be transmitted in said storing unit according to the order of addresses of said storing unit, and said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to read said data to be transmitted.

**46. (Twice Amended)** A receiving apparatus with a de-interleaving function, comprising:

a de-spreading unit for separating a desired signal from a received signal using a de-spreading code;

a data extracting unit for extracting received data from the signal separated by the de-spreading unit;

a de-interleaving unit which includes a storing unit for storing said received data from said de-spreading unit, and a control unit for controlling said storing unit so that said received data is outputted from said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data;

Sub E1  
an error correction decoding unit for decoding said received data de-interleaved by said de-interleaving unit, and for correcting an error included in said received data using an error correcting code; and

an error detecting unit for detecting an error detecting bit added when said received data is transmitted on the basis of a bit structure of the error detecting bit previously set.

47. (Twice Amended) The receiving apparatus with a de-interleaving function according to claim 46, wherein said control unit comprises a write control unit for generating a write address to be used to write said received data in said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and [interchanging rows of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to write said received data, and said control unit reads said received data stored in said storing unit according to the order of addresses of said storing unit.

48. (Twice Amended) The receiving apparatus with a de-interleaving function according to claim 46, wherein said control unit writes said data to be transmitted in said storing unit according to the order of addresses of said storing unit, and said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data,] interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to read said data to be transmitted.

Sub  
E1

49. (Twice Amended) A transmitting and receiving apparatus with a interleaving and de-interleaving function, comprising:

an error detection encoding unit for encoding an error detecting bit and for adding said error detecting bit to data to be transmitted;

an error correction encoding unit for adding an error correcting code, which is to be used for error correction, to said data to be transmitted, sent from said error detection encoding unit;

an interleaving unit which includes a storing unit for storing said data to be transmitted, from said error detection encoding unit, and a control unit for controlling said storing unit so that said data to be transmitted is outputted from said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data;

209

a signal assembling unit assembles interleaved data from said interleaving unit to form a signal format suited for transmission;

a spreading unit for converting the signal sent from said signal assembling unit into a spread signal using a predetermined spreading code;

a duplexer for transmitting the spread signal from said spreading unit to an antenna;

a de-spreading unit for separating a desired signal from a received signal via said antenna and duplexer using a de-spreading code;

a data extracting unit for extracting received data from the signal separated by the de-spreading unit;

Sub  
EI

a de-interleaving unit which includes a storing unit for storing said received data from said de-spreading unit, and a control unit for controlling said storing unit so that said received data is outputted from said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data;

OG

an error correction decoding unit for decoding said received data de-interleaved by said de-interleaving unit, and for correcting an error included in said received data using an error correcting code; and

an error detecting unit for detecting an error detecting bit added when said received data is transmitted on the basis of a bit structure of the error detecting bit previously set.

**50. (Twice Amended)** The transmitting and receiving apparatus according to claim 49, wherein said control unit comprises a write control unit for generating a write address to be used to write said data to be transmitted in said storing unit with said data to be transmitted arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, and for writing said data to be transmitted in said storing unit, and said control unit reads said data to be transmitted stored in said storing unit according to the order of addresses of said storing unit.

Sub  
E1

51. (Twice Amended) The transmitting and receiving apparatus according to claim 49, wherein said control unit writes said data to be transmitted in said storing unit according to the order of addresses of said storing unit, and said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted from said storing unit with said data to be transmitted stored in said storing unit arranged in a matrix and rearranged by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to read said data to be transmitted.

52. (Twice Amended) The transmitting and receiving apparatus according to claim 49, wherein said control unit comprises a write control unit for generating a write address to be used to write said received data in said storing unit in a state before said received data was interleaved by arranging said received data in a matrix and rearranging said received data by at least one of interchanging rows of the matrix according to a predetermined order, each row representing a set of data pieces of said data, and interchanging columns of the matrix according to a predetermined order, each column representing a set of data pieces of said data, to write said received data, and said control unit reads said received data stored in said storing unit according to the order of addresses of said storing unit.

53. (Twice Amended) The transmitting and receiving apparatus according to claim 49, wherein said control unit writes said data to be transmitted in said storing unit according to the order of addresses of said storing unit, and said control unit comprises a read control unit for generating a read address to be used to read said data to be transmitted from said storing unit with said data to be transmitted stored in said storing